

**PRODUCT RANGE**
**FYSAX AMC SERIES**

| Quality Nomenclature | Product Description   | Appox thickness (mm) | Approx Width (mm) | Approx Weight (kg/sqm) | Specification Compliance                  | Packaging Wt/Roll (Kg) |
|----------------------|---|----------------------|-------------------|------------------------|---|------------------------|
| FYSAX AMC 40         | Plain weave<br>Non-metallic   | 1.8                  | 1000              | 1.20                   | DGS&D<br>G/MISC/81C<br>Commercial quality | 36-60                  |
| FYSAX AMC 41         | Plain weave<br>Non- metallic  | 2.0                  | 1000              | 1.30                   | -   | 36-60                  |
| FYSAX AMC 41(G)      | Plain weave<br>Non- metallic  | 2.0 (max)            | 1000              | 1.15                   | -   | 36-60                  |
| FYSAX AMC 42         | Plain weave<br>Heavy construction<br>Non-metallic                               | 3.2                  | 1000              | 2.5                    | -   | 50-70                  |
| FYSAX AMC 44         | Plain weave<br>Heavy construction<br>Non-metallic                               | 6.0                  | 1000              | 3.37                   | -   | 50-70                  |
| FYSAX AMC 45         | Plain weave<br>Fine finish<br>Non-metallic                                      | 1.2                  | 1000              | 1.15                   | -   | 35-45                  |
| FYSAX AMC 46 DS      | Twill weave<br>Heavy Construction<br>Non-metallic<br>Dust suppressed            | 3.2                  | 1000              | 2.69                   | IN/TC/23<br>Pattern No.<br>0414/924-5542  | 35-65                  |
| FYSAX AMC 47 DS      | Twill weave<br>Medium construction<br>Non-metallic<br>Dust suppressed           | 1.6                  | 1000              | 1.29                   | IN/TC/23<br>Pattern No.<br>0414/924-5543  | 35-65                  |
| FYSAX AMCM51         | Plain weave<br>Each strand reinforced with brass wire                           | 1.6                  | 1000              | 1.40                   | -   | 36-60                  |
| FYSAX AMCP 507       | 100% chemically pure asbestos cloth, plain and close weave, Medium construction | 2.0                  | 1000              | 2.4                    | -   | 45-80                  |
| FYSAX AMCP 508       | 100% chemically pure asbestos cloth, plain and close weave, Heavy construction  | 3.2                  | 1000              | 2.8                    | -   | 45-80                  |

*The sizes are theoretic and indicative. Applicable tolerance  $\pm 10\%$  if not covered by specifications.*